

# STAINLESS STEEL WIRE

Straightened stainless steel wire		
Diameter	Tolerance	Material
mm	mm	AISI
0.15	-0.01	304
0.20	-0.01	304, 316L
0.25	-0.01	304
0.30	-0.01	304, 316L
0.35	-0.01	304
0.40	-0.015	302
0.45	-0.015	302
0.50	-0.015	302, 316L
0.52	-0.015	302
0.55	-0.015	302
0.60	-0.015	302, 316L
0.65	-0.015	302
0.66	-0.015	302
0.67	-0.015	302
0.70	-0.015	302
0.75	-0.015	302
0.80	-0.015	302
0.85	-0.015	302
0.90	-0.015	302
0.95	-0.015	302
1.00	-0.015	302, 316L
1.10	-0.015	302, 304
1.20	-0.015	302
1.30	-0.015	302, 316L
1.40	-0.015	302, 316L
1.50	-0.015	302, 316L
1.60	-0.015	302
1.70	-0.015	302
1.80	-0.015	302
1.90	-0.015	304, 316L
2.00	-0.015	302, 316L
2.10	-0.015	316L
2.20	-0.015	302
2.25	-0.015	304
2.30	-0.015	316L



2.40	-0.015	302, 316L
2.50	-0.015	303, 316L
2.60	-0.015	303, 316L
2.80	-0.015	303
3.00	-0.015	303, 316L
3.50	-0.02	303, 316L
4.00	-0.02	303, 316L

*The tolerances mentioned above are given for information purpose only. The contracted tolerances can be adapted to your needs and will be confirmed in our offers.*

Updated January 24, 2019

---

Unimed SA  
Rue de Grand-Pré 10  
CH-1007 Lausanne

Tel : +41 21 624 21 51  
Fax : +41 21 624 53 32